



STRONGHOLD 6" (152mm)
STANDARD FORM UNIT

WATERPROOF
MEMBRANE

BACKFILL AS SPECIFIED
(FREE DRAINING)

3/4" (19mm) CRUSHED
STONE OVER PIPE
AS PER CODE OR
AS SPECIFIED

CONTINUOUS PERFORATED
DRAIN TILE AS PER SPECS

VARIES

CONTINUOUS CONCRETE
FOOTING ON UNDISTURBED
SOIL (FOOTING SIZE AND
REINFORCEMENT AS PER
CODE OR AS SPECIFIED)

#4 REBAR HORIZ/VERT
REINFORCEMENT
AS PER CODE
OR AS SPECIFIED

MIN 1/2" (13mm)
GYPSUM BOARD OR
OTHER APPROVED
THERMAL BARRIER

4" (102mm) MIN
CONCRETE SLAB
AS PER CODE OR
AS SPECIFIED

COMPACTED GRANULAR FILL



STRONGHOLD
INSULATED CONCRETE FORMS
BUILD TRUST
WWW.STRONGHOLDICF.COM

THESE TABLES AND DRAWINGS ARE PROVIDED AS A REFERENCE GUIDE FOR USE BY DESIGNERS. THE USE IS RESPONSIBLE FOR MODIFYING THE DRAWING AND INFORMATION AS NEEDED TO MEET APPLICABLE BUILDING CODE AND CONSTRUCTION PRACTICES. STRONGHOLD RESERVES THE RIGHT TO MAKE CHANGES TO THE DRAWINGS WITHOUT NOTICE AND ASSUMES NO LIABILITY IN CONNECTION WITH THE USE OF THIS DRAWING INCLUDING MODIFICATIONS, COPYING OR DISTRIBUTION.

DRAWN: NILLES C.	DATE: 10/25/2019	DRAWING TYPE: DETAIL
TITLE: 6 IN STRONGHOLD WALL - SLAB BELOW GRADE		